



The COLDTAINER product line includes a large range of state of the art 12V active mobile refrigerated containers. The containers are produced using the rotational molding technology according to the highest standards. They come in a variety of types, internal volumes and internal temperature ranges designed to satisfy all possible demands of professional users in term of temperature controlled transport

- Internal gross capacity 565 litres
- Special versions with internal gel battery and battery charger for full "Autonomous Operation" without any connection to the vehicle's battery. The internal battery is rechargeable from the AC mains thanks to the included charger
- The ideal solution for refrigerated transport on board of electric vehicles
- Single piece design is sturdy, durable and lightweight, with no junctions or cold bridges. Made of food grade polyethylene (PE), UV stabilized. Ultra-thick insulation made by PU foam. Designed for an easy cleaning and disinfection
- Refrigeration system includes 12V compressors, large surface roll-bond evaporators, ventilated high efficiency spiral tube condensers, electronic thermostat with digital display
- NDH version available for the safe transport of sensitive products (i.e. pharmaceuticals, vaccines, blood). It maintains consistent temperature with a smooth air flow distribution, regardless of outside ambient temperature in alignment with GDP

Available versions:

 NDN down to +0°C

 FDN down to -21°C

 NDH from +30°C to +0°C



easy cooling, smart moving

www.coldtainer.com

F0565

PRODUCT INFO

Model name	F0565/NDN AuO	F0565/FDN AuO	F0565/NDH AuO
EE article nr.	817012/00	817012/01	817012/02
Gross capacity (Lt)	565	565	565
Temperature range (°C)*	down to +0 °C	down to -21 °C	from +30 °C to +0 °C
ATP class	FRAX	FRCX	BRBX
Voltage	12 Vdc	12 Vdc	12 Vdc
Internal battery	VRLA 12Vdc 165Ah	VRLA 12Vdc 165Ah	VRLA 12Vdc 165Ah
External dimensions (mm)	725 x 1220 x 1650	725 x 1220 x 1650	725 x 1220 x 1650
Weight (kg)	194	202	207
PU insulation (mm)	100	100	100
"K" insulation factor	0,31 W/m²K	0,31 W/m²K	0,31 W/m²K
Refrigerant gas (type)	R134a	R452A	R134a
Refrigerant gas (gr)	135	212	133

*with ambient temperature +30°C

E57

10R-060148

102025 rev01 - Copyright©2025 Euroengel srl

